



S A F E T Y W E A R

2021 CATALOGUE - VOL 1



E N G I N E E R E D W I T H P U R P O S E



E N G I N E E R E D W I T H P U R P O S E

BOVA cemented their reputation in Africa by delivering high quality engineering through their range of safety footwear. 21 years after producing their first safety boot, BOVA extended their portfolio to include work wear and fall arrest systems.

When designing new products, we explore the varied dangers inherent in an industry and then engineer the product purposed with protecting employees within those environments. For procurement and those we protect, this means utilising our category ranges to ensure that the required safety needs are met. Different employees within the same industry often require very different levels of protection. Through an understanding of the varied dangers faced by an employee in their work environment and applying the correct product, clients can ensure that they do not under-spec for some employees, thereby compromising on safety or over-spec for others – and compromise on cost-effectiveness.

All Bova products are manufactured in ISO 9001 accredited facilities, utilising cutting-edge technology and innovations. In this way, we can ensure that what we release into the market performs with the purpose for which it was engineered.

BOVA EPITOMISES ENGINEERED EXCELLENCE, WITH A CLEAR PURPOSE.

CONTENTS

FOOTWEAR	PG 6-13
LIGHTWEAR RANGE	PG 6
• EXECUTIVE	PG 6
• UTILTY	PG 6
HEAVYWEAR RANGE	PG 7-9
• CORE	PG 6-7
• TRAX	PG 8
• AKTIV	PG 8
• CUTRANGE	PG 9
EXTREMEWEAR RANGE	PG 9-12
• PU/RUBBER	PG 9-11
• RUBBER/RUBBER	PG 11-12
PARAMILITARY RANGE	PG 12-13
• LEATHER	PG 12
• CANVAS	PG 13
FALL ARREST	PG 14-20
HARNES WITH LANYARD RANGE	PG 15-17
• CORE	PG 15-16
• CORE+	PG 16-17
HARNES RANGE	PG 17-18
• UNDERGROUND MINING	PG 17
• MULTI-PURPOSE	PG 17
• ROPE ACCESS & RESCUE	PG 17
• SPECIALISED HARNESSES	PG 18
BELT RANGE	PG 18
• MINERS	PG 18
LANYARD RANGE	PG 19-20
• STANDARD LANYARDS	PG 19-20
• SPECIALISED LANYARDS	PG 20
WORKWEAR	PG 21-25
CONTISUIT RANGE	PG 22-24
• 65/35 POLYCOTTON	PG 22
• POLYVISCOSE	PG 23
• J54 100% COTTON	PG 23
• DENIM CONTISUITS	PG 24
• D59 100% COTTON	PG 24
• HIGHVIZ	PG 24
BOILERSUIT RANGE	PG 25
• J54 100% COTTON	PG 25
• D59 100% COTTON	PG 25
DUST COAT RANGE	PG 25
• 65/35 POLYCOTTON	PG 25
• ACID RESISTANT	PG 25
HIGH VISIBILITY SHIRTS RANGE	PG 25
• SHIRTS	PG 25
SIZE CHART	PG 26
CHEMICAL RESISTANCE TABLE	PG 27



INNOVATIVE SOLING TECHNOLOGIES




ENGINEERED WITH PURPOSE

LIGHTYWEAR RANGE
Durable safety solutions for everyday light business hazards

EXECUTIVE RANGE

CAMBRIDGE: 70004♂



Sizes
5-12

Colour
Black


SPECIFIC FEATURES:

TOE CAP: Steel
SOLE: Single Density PU (Heat resistant up to 95°C)
MIDSOLE: Shank reinforcement for arch support
SANS / ISO 20345

LIGHTYWEAR RANGE
Durable safety solutions for everyday light business hazards

EXECUTIVE RANGE

OXFORD: 70006♂



Sizes
5-12

Colour
Black


SPECIFIC FEATURES:

TOE CAP: Steel
SOLE: Single Density PU (Heat resistant up to 95°C)
MIDSOLE: Shank reinforcement for arch support
SANS / ISO 20345

LIGHTYWEAR RANGE
Durable safety solutions for everyday light business hazards

UTILITY RANGE

ADAPT: 71442♂



Sizes
5-13

Colour
Black


SPECIFIC FEATURES:

TOE CAP: Steel
SOLE: Single Density PU (Heat resistant up to 95°C)
MIDSOLE: Shank reinforcement for arch support
SANS / ISO 20345 NRCS/9002/287766/0119

LIGHTYWEAR RANGE
Durable safety solutions for everyday light business hazards

EXECUTIVE RANGE

JARMAN: 70003♂



Sizes
5-12

Colour
Black


SPECIFIC FEATURES:

TOE CAP: Steel
SOLE: Single Density PU (Heat resistant up to 95°C)
MIDSOLE: Shank reinforcement for arch support
SANS / ISO 20345

LIGHTYWEAR RANGE
Durable safety solutions for everyday light business hazards

UTILITY RANGE

MULTI: 71441♂



Sizes
5-13

Colour
Black


SPECIFIC FEATURES:

TOE CAP: Steel
SOLE: Single Density PU (Heat resistant up to 95°C)
MIDSOLE: Shank reinforcement for arch support
SANS / ISO 20345 NRCS/9002/287766/0120

LIGHTYWEAR RANGE
Durable safety solutions for everyday light business hazards

CORERANGE

TRAINER: 60012♂



Sizes
4-12

Colour
Black

SPECIFIC FEATURES:

TOE CAP: Steel
SOLE: Dual Density PU/PU (Heat-resistant up to 95°C)
MIDSOLE: Shank reinforcement for arch support
SANS / ISO 20345 NRCS/9002/287766/0171

CORERANGE

MAVERICK: 60002♂



ANTI-STATIC

CE

Ultrashock

Sizes
4-13

Colour
Black

SPECIFIC FEATURES:

TOE CAP: Steel
SOLE: Dual Density PU/PU (Heat resistant up to 95°C)
MIDSOLE: SMS available (60702)

EN / ISO 20345 NRCS/9002/287766/0169

CORERANGE

NEOFLEX: 90004♂



ANTI-STATIC

EXTENDED SIZE RANGE

CE

Ultrashock

Sizes
3-15

Colour
Black & Richmond (MTO)

SPECIFIC FEATURES:

TOE CAP: Steel / Available without toe cap in Black only (90504)
SOLE: Dual Density PU/PU (Heat resistant up to 95°C)
MIDSOLE: SMS available (90704 / Black only)

EN / ISO 20345 NRCS/9002/287766/0055

CORERANGE

CHELSEA: 90006♂



ANTI-STATIC

CE

Ultrashock

Sizes
3-13

Colour
Black & Brown

SPECIFIC FEATURES:

TOE CAP: Steel / Available without toe cap (90506 / MTO)
SOLE: Dual Density PU/PU (Heat resistant up to 95°C)
MIDSOLE: APT midsole available (90606)

EN / ISO 20345 NRCS/9002/287766/0170

CORERANGE

RADICAL: 60001♂



ANTI-STATIC

CE

Ultrashock

Sizes
4-13

Colour
Black

SPECIFIC FEATURES:

TOE CAP: Steel
SOLE: Dual Density PU/PU (Heat resistant up to 95°C)
MIDSOLE: Shank reinforcement for arch support

EN / ISO 20345 NRCS/9002/287766/0165

CORERANGE

NEOGRIP: 90005♂



ANTI-STATIC

CE

Ultrashock

Sizes
5-13

Colour
Black & Richmond (MTO)

SPECIFIC FEATURES:

TOE CAP: Steel / Available without toe cap (90505 / Black only / MTO)
SOLE: Dual Density PU/PU (Heat resistant up to 95°C)
MIDSOLE: SMS available (90705 / Black only / MTO)

EN / ISO 20345 NRCS/9002/287766/0117

CORERANGE

HAMBURG: 90008♂



ANTI-STATIC

SABS APPROVED

Ultrashock

Sizes
4-12

Colour
Grey

SPECIFIC FEATURES:

TOE CAP: Steel
SOLE: Dual Density PU/PU (Heat resistant up to 95°C)
MIDSOLE: Shank reinforcement for arch support

SANS / ISO 20345 NRCS/9002/287766/0116

TRAX RANGE

MUNICH: 20002♂



ANTI-STATIC

SABS APPROVED

Ultrashock

Sizes
5-13

Colour
Black

SPECIFIC FEATURES:

TOE CAP: Steel - Extra-wide Fitting
SOLE: Dual Density PU/PU (Heat resistant up to 95°C)
MIDSOLE: SMS available (20702)

SANS / ISO 20345 NRCS/9002/287766/0161

TRAX RANGE

HIKER: 20013♂



ANTI-STATIC

SABS APPROVED

Ultrashock

Sizes
3-13

Colour
Black & Walnut

SPECIFIC FEATURES:

TOE CAP: Steel - extra wide fitting / Available without toe cap (20513 / Walnut only / MTO)
SOLE: Dual Density PU/PU (Heat resistant up to 95°C)
MIDSOLE: Shank reinforcement for arch support

SANS / ISO 20345 NRCS/9002/287766/0146

AKTIV RANGE

COLUMBIA: 30005♂



ANTI-STATIC

METAL FREE

SABS APPROVED

Ultrashock

Sizes
5-12

Colour
Black

SPECIFIC FEATURES:

TOE CAP: Composite
SOLE: Dual Density PU/PU (Heat resistant up to 95°C)
MIDSOLE: Shank reinforcement for arch support

SANS / ISO 20345

TRAX RANGE

BREMEN: 20001♂



ANTI-STATIC

SABS APPROVED

Ultrashock

Sizes
5-13

Colour
Black

SPECIFIC FEATURES:

TOE CAP: Steel - Extra-wide Fitting
SOLE: Dual Density PU/PU (Heat resistant up to 95°C)
MIDSOLE: SMS available (20701)

SANS / ISO 20345 NRCS/9002/287766/0162

TRAX RANGE

HEALTH SANDAL: 20011♂



ANTI-STATIC

RECOMMENDED FOR INDIVIDUALS WITH DIABETES

SABS APPROVED

Ultrashock

Sizes
5-12

Colour
Rust

SPECIFIC FEATURES:

TOE CAP: Steel - Extra-wide Fitting
SOLE: Dual Density PU/PU (Heat resistant up to 95°C)
MIDSOLE: Shank reinforcement for arch support

SANS / ISO 20345

AKTIV RANGE

ATLANTIS: 30006♂



ANTI-STATIC

METAL FREE

SABS APPROVED

Ultrashock

Sizes
5-12

Colour
Black

SPECIFIC FEATURES:

TOE CAP: Composite
SOLE: Dual Density PU/PU (Heat resistant up to 95°C)
MIDSOLE: Shank reinforcement for arch support

SANS / ISO 20345

CUTRANGE

DAKOTA: 40002♂



ANTI-STATIC

SABS APPROVED

Ultrashock

FREE FROM TOXIC

Sizes 5-12

Colour Black

SPECIFIC FEATURES:

TOE CAP: Steel
SOLE: Dual Density PU/PU (Heat resistant up to 95°C)
MIDSOLE: Shank reinforcement for arch support

SANS / ISO 20345

PURUBBERANGE

FIREWALK: 42003♂



ELECTRICAL RESISTANCE TO 20 KVA FOR 60 SECONDS (ESKOM SPEC 34-232)

NON CONDUCTIVE

SABS APPROVED

Ultrashock

FREE FROM TOXIC

Sizes 4-13

Colour Black

SPECIFIC FEATURES:

TOE CAP: Steel
SOLE: Dual Density PU/Rubber (Heat resistant up to 300°C)
MIDSOLE: APT midsole available (42603)

SANS / ISO 20345 NRCS/9002/287766/0134

PURUBBERANGE

RIGGER: 42770♂



NON CONDUCTIVE

ENGINEERED FOR THE OIL INDUSTRY

SABS APPROVED

Ultrashock

FREE FROM TOXIC

Sizes 5-13

Colour Black

SPECIFIC FEATURES:

TOE CAP: Steel
SOLE: Dual Density PU/Rubber (Heat resistant up to 300°C)
MIDSOLE: Standard with SMS

SANS / ISO 20345

PURUBBERANGE

METAGUARD: 42005♂



NON CONDUCTIVE

WITH METATARSAL PROTECTION ENGINEERING

SABS APPROVED

Ultrashock

FREE FROM TOXIC

Sizes 4-13

Colour Black

SPECIFIC FEATURES:

TOE CAP: Steel
SOLE: Dual Density PU/Rubber (Heat resistant up to 300°C)
MIDSOLE: Shank reinforcement for arch support

SANS / ISO 20345

PURUBBERANGE

WELDERS: 42004♂



NON CONDUCTIVE

WITH SPAT COVERING

SABS APPROVED

Ultrashock

FREE FROM TOXIC

Sizes 4-13

Colour Black

SPECIFIC FEATURES:

TOE CAP: Steel
SOLE: Dual Density PU/Rubber (Heat resistant up to 300°C)
MIDSOLE: APT midsole available (42604 / MTO)

SANS / ISO 20345

PURUBBERANGE

FREEZER: 42018♂



NON CONDUCTIVE

3M THINSULATE MATERIAL

SABS APPROVED

Ultrashock

FREE FROM TOXIC

Sizes 5-13

Colour Black

SPECIFIC FEATURES:

TOE CAP: Steel
SOLE: Dual Density PU/Rubber (Cold resistant down to -25°C)
MIDSOLE: APT midsole available (42618 / MTO)

SANS / ISO 20345

PURUBBERANGE

SMELTERS BUCKLE: 42007♂



NON CONDUCTIVE

WITH KEVLAR FEATURES

CE

Ultrashock

FREE FROM TOXIC

Sizes 4-13

Colour Black

SPECIFIC FEATURES:

TOE CAP: Aluminium
SOLE: Dual Density PU/Rubber (Heat resistant up to 300°C)
MIDSOLE: APT midsole available (42607 / MTO)

EN / ISO 20345

PURUBBERANGE

SMELTERS METAGUARD: 42008♂



NON CONDUCTIVE

WITH KEVLAR FEATURES

SABS APPROVED

Ultrashock

FREE FROM TOXIC

WITH METATARSAL PROTECTION ENGINEERING

Sizes 4-13

Colour Black

SPECIFIC FEATURES:

TOE CAP: Aluminium
SOLE: Dual Density PU/Rubber (Heat resistant up to 300°C)
MIDSOLE: Shank reinforcement for arch support

SANS / ISO 20345

PURUBBERANGE

DROGUE: 43602♂



NON CONDUCTIVE

SRC SLIP RESISTANCE RATING

SABS APPROVED

Ultrashock

FREE FROM TOXIC

ELECTRICAL RESISTANCE TO 20 KVA FOR 60 SECONDS (ESKOM SPEC 34-232)

Sizes 4-13

Colour Black

SPECIFIC FEATURES:

TOE CAP: Steel - Extra-wide Fitting
SOLE: Dual Density PU/Vibram Rubber (Heat resistant up to 300°C)
MIDSOLE: Standard with APT

SANS / ISO 20345

PURUBBERANGE

SMELTERS VELCRO: 42006♂



NON CONDUCTIVE

WITH KEVLAR FEATURES

CE

Ultrashock

FREE FROM TOXIC

Sizes 4-13

Colour Black

SPECIFIC FEATURES:

TOE CAP: Aluminium
SOLE: Dual Density PU/Rubber (Heat resistant up to 300°C)
MIDSOLE: APT midsole available (42604 / MTO)

EN / ISO 20345

PURUBBERANGE

NEBULA: 43603♂



NON CONDUCTIVE

SRC SLIP RESISTANCE RATING

SABS APPROVED

Ultrashock

FREE FROM TOXIC

ELECTRICAL RESISTANCE TO 20 KVA FOR 60 SECONDS (ESKOM SPEC 34-232)

Sizes 4-13

Colour Brown

SPECIFIC FEATURES:

TOE CAP: Steel - Extra-wide Fitting
SOLE: Dual Density PU/Vibram Rubber (Heat resistant up to 300°C)
MIDSOLE: Standard with APT

SANS / ISO 20345

PURUBBERANGE

ROCNA: 43601♂



NON CONDUCTIVE

SRC SLIP RESISTANCE RATING

SABS APPROVED

Ultrashock

FREE FROM TOXIC

ELECTRICAL RESISTANCE TO 20 KVA FOR 60 SECONDS (ESKOM SPEC 34-232)

Sizes 4-13

Colour Black

SPECIFIC FEATURES:

TOE CAP: Steel - Extra-wide Fitting
SOLE: Dual Density PU/Vibram Rubber (Heat resistant up to 300°C)
MIDSOLE: Standard with APT

SANS / ISO 20345

PURUBBER RANGE
SIERRA: 43604 ♂



- NON CONDUCTIVE
- SRC SLIP RESISTANCE RATING
- ELECTRICAL RESISTANCE TO 20 KVA FOR 60 SECONDS (ESKOM SPEC 34-232)
- FREE SOLING
- SABBS APPROVED
- Ultraclean
- Sizes 4-13
- Colour Tan

SPECIFIC FEATURES:
TOE CAP: Steel - Extra-wide Fitting
SOLE: Dual Density PU/Vibram Rubber (Heat resistant up to 300°C)
MIDSOLE: Standard with APT
SANS / ISO 20345

RUBBER/RUBBER RANGE
BASALT: 7142 ♂



- ANTI-STATIC
- 300°C DIRECT & RADIANT HEAT RESISTANT
- SRC SLIP RESISTANCE RATING
- 100% WATERPROOF SOLE
- Ultraclean
- Sizes 4-14
- Colour Black

SPECIFIC FEATURES:
TOE CAP: Steel
SOLE: Dual Compound Rubber / Rubber (Heat resistant up to 300°C)
EN / ISO 20345

RUBBER/RUBBER RANGE
SLATE: 7144 ♂



- ANTI-STATIC
- 300°C DIRECT & RADIANT HEAT RESISTANT
- SRC SLIP RESISTANCE RATING
- 100% WATERPROOF SOLE
- Ultraclean
- Sizes 4-14
- Colour Black

SPECIFIC FEATURES:
TOE CAP: Aluminium
SOLE: Dual Compound Rubber (Heat resistant up to 300°C)
EN/ISO 20345

RUBBER/RUBBER RANGE
MARBLE: 7141 ♂



- ANTI-STATIC
- 300°C DIRECT & RADIANT HEAT RESISTANT
- SRC SLIP RESISTANCE RATING
- 100% WATERPROOF SOLE
- Ultraclean
- Sizes 4-14
- Colour Black

SPECIFIC FEATURES:
TOE CAP: Steel
SOLE: Dual Compound Rubber / Rubber (Heat resistant up to 300°C)
EN / ISO 20345

RUBBER/RUBBER RANGE
TASONITE: 7100 ♂



- ANTI-STATIC
- 300°C DIRECT & RADIANT HEAT RESISTANT
- SRC SLIP RESISTANCE RATING
- 100% WATERPROOF SOLE
- Ultraclean
- Sizes 4-14
- Colour Black

SPECIFIC FEATURES:
TOE CAP: Steel
SOLE: Dual Compound Rubber / Rubber (Heat resistant up to 300°C)
EN / ISO 20345

RUBBER/RUBBER RANGE
GABBRO: 7140 ♂



- ANTI-STATIC
- 300°C DIRECT & RADIANT HEAT RESISTANT
- SRC SLIP RESISTANCE RATING
- 100% WATERPROOF SOLE
- Ultraclean
- Sizes 4-14
- Colour Black

SPECIFIC FEATURES:
TOE CAP: Steel
SOLE: Dual Compound Rubber / Rubber (Heat resistant up to 300°C)
EN / ISO 20345

RUBBER/RUBBER RANGE
GRANITE: 7900 ♂



- 100% WATERPROOF SOLE
- ANTI-STATIC
- SABBS APPROVED
- Ultraclean
- Sizes 6-13
- Colour Black

SPECIFIC FEATURES:
TOE CAP: No toe cap
SOLE: Dual Compound Rubber / Rubber (Heat resistant up to 300°C)
SANS / ISO 20345

RUBBER/RUBBER RANGE
PATRIOT: 7010 ♂



- 100% WATERPROOF SOLE
- ANTI-STATIC
- SABBS APPROVED
- Ultraclean
- Sizes 6-13
- Colour Black

SPECIFIC FEATURES:
TOE CAP: No toe cap
SOLE: Dual Compound Rubber / Rubber (Heat resistant up to 300°C)
SANS / ISO 20345

LEATHER RANGE
SWAT: 90561 ♂



- ANTI-STATIC
- SABBS APPROVED
- Ultraclean
- Sizes 3-13
- Colour Black & Walnut

SPECIFIC FEATURES:
TOE CAP: No toe cap / available with STC (90461)
SOLE: Double Density PU/PU (Heat resistant up to 95°C)
MIDSOLE: SMS available (90761)
SANS / ISO 20345

RUBBER/RUBBER RANGE
IGNEOUS: 7150 ♂



- ANTI-STATIC
- 300°C DIRECT & RADIANT HEAT RESISTANT
- SRC SLIP RESISTANCE RATING
- 100% WATERPROOF SOLE
- Ultraclean
- Sizes 4-14
- Colour Black

SPECIFIC FEATURES:
TOE CAP: Steel
SOLE: Dual Compound Rubber / Rubber (Heat resistant up to 300°C)
EN / ISO 20345

LEATHER RANGE
PATROL: 90443 ♂



- ANTI-STATIC
- SABBS APPROVED
- Ultraclean
- Sizes 3-13
- Colour Black

SPECIFIC FEATURES:
TOE CAP: Steel / Available without toe cap (90543)
SOLE: Double Density PU/Rubber (Heat resistant up to 95°C)
SANS / ISO 20345

LEATHER RANGE
POLICE: 90498 ♂



- ANTI-STATIC
- CE
- Ultraclean
- Sizes 3-13
- Colour Black

SPECIFIC FEATURES:
TOE CAP: Steel / Available without toe cap (90598)
SOLE: Double Density PU/PU (Heat resistant up to 95°C)
EN / ISO 20345



PARAMILITARY RANGE

Purpose-engineered safety boots for security, paramilitary and policing operations

CANVAS RANGE

GUARD: 83006 ♂



Sizes

4-13

Colour

Black

Nutria, Navy,
Green (MOQ)

SPECIFIC FEATURES:

TOE CAP: No toe cap

SOLE: Single Density PU (Heat resistant up to 95°C)

SANS / ISO 20345



PARAMILITARY RANGE

Purpose-engineered safety boots for security, paramilitary and policing operations

CANVAS RANGE

RANGER: 83029 ♂



Sizes

4-13

Colour

Black

Nutria, Navy,
Green (MOQ)

SPECIFIC FEATURES:

TOE CAP: No toe cap

SOLE: Single Density PU (Heat resistant up to 95°C)

SANS / ISO 20345



BOVA

FOOTWEAR



BOVA

FALLARREST



ENGINEERED WITH PURPOSE

HARNES WITH LANYARD RANGE CORE

CODE: HARN01260

STANDARD HARNES
DOUBLE LEG LANYARD WITH SCAFF HOOKS
WITH SANDING STEP



SPECIFIC FEATURES:

- SIZING:** • ONE SIZE FITS ALL
STANDARDS: • SANS 50354 | EN 354
 SANS 50355 | EN 355
 SANS 50361 | EN 361
 EN 362
FEATURES: • Adjustable leg & chest straps
 • Shock absorbing lanyard

MATERIALS:



- Harness Webbing:** • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes
Lanyard Webbing: • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes
 • Lanyard length: 1 750mm
 • Lanyard length when shock absorber is fully elongated: 3 450mm
Chest Strap: • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes
Buckles: • Interlocking, corrosion-resistant steel buckles
Hooks: • Corrosion-resistant steel scaffolding hooks with 50mm gate opening

HARNES WITH LANYARD RANGE CORE

CODE: HARN01250

STANDARD HARNES
DOUBLE LEG LANYARD WITH SNAP HOOKS
WITH SANDING STEP



SPECIFIC FEATURES:

- SIZING:** • ONE SIZE FITS ALL
STANDARDS: • SANS 50354 | EN 354
 SANS 50355 | EN 355
 SANS 50361 | EN 361
 EN 362
FEATURES: • Adjustable leg & chest straps
 • Shock absorbing lanyard

MATERIALS:



- Harness Webbing:** • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes
Lanyard Webbing: • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes
 • Lanyard length: 1 750mm
 • Lanyard length when shock absorber is fully elongated: 3 450mm
Chest Strap: • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes
Buckles: • Interlocking, corrosion-resistant steel buckles
Hooks: • Corrosion-resistant steel snap hooks with 20mm gate opening

HARNES WITH LANYARD RANGE CORE

CODE: HARN01220

STANDARD HARNES
DOUBLE LEG LANYARD WITH SCAFF HOOKS



SPECIFIC FEATURES:

- SIZING:** • ONE SIZE FITS ALL
STANDARDS: • SANS 50354 | EN 354
 SANS 50355 | EN 355
 SANS 50361 | EN 361
 EN 362
FEATURES: • Adjustable leg & chest straps
 • Shock absorbing lanyard

MATERIALS:



- Harness Webbing:** • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes
Lanyard Webbing: • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes
 • Lanyard length: 1750mm
 • Lanyard length when shock absorber is fully elongated: 3 450mm
Chest Strap: • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes
Buckles: • Interlocking, corrosion-resistant steel buckles
Hooks: • Corrosion-resistant steel scaffolding hooks with 50mm gate opening

HARNES WITH LANYARD RANGE CORE

CODE: HARN01210

STANDARD HARNES
DOUBLE LEG LANYARD WITH SNAP HOOKS



SPECIFIC FEATURES:

- SIZING:** • ONE SIZE FITS ALL
STANDARDS: • SANS 50354 | EN 354
 SANS 50355 | EN 355
 SANS 50361 | EN 361
 EN 362
FEATURES: • Adjustable leg & chest straps
 • Shock absorbing lanyard

MATERIALS:



- Harness Webbing:** • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes
Lanyard Webbing: • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes
 • Lanyard length: 1 750mm
 • Lanyard length when shock absorber is fully elongated: 3 450mm
Chest Strap: • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes
Buckles: • Interlocking, corrosion-resistant steel buckles
Hooks: • Corrosion-resistant steel snap hooks with 20mm gate opening

HARNES WITH LANYARD RANGE CORE

CODE: HARN01110

NON BELTED HARNES
SINGLE LEG LANYARD WITH SNAP HOOK



SPECIFIC FEATURES:

- SIZING:** • ONE SIZE FITS ALL
STANDARDS: • SANS 50354 | EN 354
 SANS 50355 | EN 355
 SANS 50361 | EN 361
 EN 362
FEATURES: • Adjustable leg & chest straps
 • Shock absorbing lanyard

MATERIALS:



- Harness Webbing:** • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes
Lanyard Webbing: • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes
 • Lanyard length: 1 750mm
 • Lanyard length when shock absorber is fully elongated: 3 450mm
Chest Strap: • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes
Buckles: • Interlocking, corrosion-resistant steel buckles
Hooks: • Corrosion-resistant steel snap hooks with 20mm gate opening

HARNES WITH LANYARD RANGE CORE

CODE: HARN02260

BELTED HARNES
DOUBLE LEG LANYARD WITH SCAFF HOOKS
WITH SANDING STEP



SPECIFIC FEATURES:

- SIZING:** • ONE SIZE FITS ALL
STANDARDS: • SANS 50354 | EN 354
 SANS 50355 | EN 355
 SANS 50361 | EN 361
 EN 362
FEATURES: • Adjustable shoulder, leg, waist & chest straps
 • Shock absorbing lanyard

MATERIALS:



- Harness Webbing:** • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes
Lanyard Webbing: • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes
 • Lanyard length: 1 750mm
 • Lanyard length when shock absorber is fully elongated: 3 450mm
Chest Strap: • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes
Buckles: • Interlocking, corrosion-resistant steel buckles
Hooks: • Corrosion-resistant steel scaffolding hooks with 50mm gate opening

HARNES WITH LANYARD RANGE CORE

CODE: HARN01000

FULL BODY HARNES
WITH SANDING STEP



SPECIFIC FEATURES:

- SIZING:** • ONE SIZE FITS ALL
STANDARDS: • SANS 50361 | EN 361
FEATURES: • Adjustable leg & chest straps

MATERIALS:



- Harness Webbing:** • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes
Chest Strap: • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes
Buckles: • Interlocking, corrosion-resistant steel buckles
Hooks: • Corrosion-resistant steel snap hooks with 20mm gate opening

HARNES WITH LANYARD RANGE - CORE

CODE: HARN02220

BELTED HARNES
DOUBLE LEG LANYARD WITH SCAFF HOOKS



SPECIFIC FEATURES:

- SIZING:** • ONE SIZE FITS ALL
STANDARDS: • SANS 50354 | EN 354
 SANS 50355 | EN 355
 SANS 50361 | EN 361
 EN 362
FEATURES: • Adjustable shoulder, leg, waist & chest straps
 • Shock absorbing lanyard

MATERIALS:



- Harness Webbing:** • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes
Lanyard Webbing: • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes
 • Lanyard length: 1 750mm
 • Lanyard length when shock absorber is fully elongated: 3 450mm
Chest Strap: • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes
Buckles: • Interlocking, corrosion-resistant steel buckles
Hooks: • Corrosion-resistant steel scaffolding hooks with 50mm gate opening

HARNES WITH LANYARD RANGE CORE*

CODE: HARN02210

BELTED HARNES DOUBLE LEG LANYARD WITH SNAP HOOKS



SPECIFIC FEATURES:

- SIZING:** • ONE SIZE FITS ALL
- STANDARDS:** • SANS 50354 | EN 354
SANS 50355 | EN 355
SANS 50361 | EN 361
EN 362
- FEATURES:** • Adjustable shoulder, leg, waist & chest straps
• Shock absorbing lanyard

MATERIALS:



Harness Webbing: • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes

Lanyard Webbing: • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes
• Lanyard length: 1 750mm
• Lanyard length when shock absorber is fully elongated: 3 450mm

Chest Strap: • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes

Buckles: • Interlocking, corrosion-resistant steel buckles

Hooks: • Corrosion-resistant steel snap hooks with 20mm gate opening

HARNES RANGE - MULTI-PURPOSE

AGILIS - HARN40000

MULTI-PURPOSE HARNES



SPECIFIC FEATURES:

- SIZING:** • S | M | L | XL
- STANDARDS:** • SANS 50361 | EN 361
SANS 50358 | EN 358
- FEATURES:** • 4 attachment points: Chest & dorsal D-ring attachment points with work positioning D-rings
• Adjustable leg, waist, shoulder & chest straps
• Padded waist
• Standing step

MATERIALS:



Harness Webbing: • 45mm UV-Resistant polyester webbing with a minimum breaking load of 2,6 tonnes

Padding: • 5mm laminated foam to spread pressure over a larger area

Buckles: • Interlocking, corrosion-resistant steel buckles

HARNES RANGE - UNDERGROUND MINING

EXCAVO - HARN30000

MINING HARNES



SPECIFIC FEATURES:

- SIZING:** • S | M | L | XL
- STANDARDS:** • SANS 50361 | EN 361
- FEATURES:** • Rescue pack & battery straps
• 3 attachment points: Dorsal D-ring & 2 frontal attachment points
• Adjustable leg, shoulder, chest & waist straps
• Padded waist & shoulder straps
• Standing step

MATERIALS:



Harness Webbing: • 45mm UV-Resistant polyester webbing with a minimum breaking load of 2,6 tonnes

Padding: • 5mm laminated foam to spread pressure over a larger area

Buckles: • Interlocking, corrosion-resistant steel buckles

HARNES RANGE ROPE ACCESS & RESCUE

GORDIAN - HARN50000

ROPE ACCESS & RESCUE HARNES



SPECIFIC FEATURES:

- SIZING:** • S | M | L | XL
- STANDARDS:** • SANS 50361 | EN 361
SANS 50358 | EN 358
SANS 50813 | EN 813
- FEATURES:** • 5 attachment points: Front waist, chest & dorsal D-ring attachment points with work positioning D-rings & loops
• Adjustable leg, shoulder, back, chest & waist straps
• Padding in the leg & waist areas

MATERIALS:



Harness Webbing: • 45mm UV-Resistant polyester webbing with a minimum breaking load of 2,6 tonnes

Padding: • 5mm laminated foam to spread pressure over a larger area

Buckles: • Interlocking, corrosion-resistant steel buckles

Front Connector: • Steel screw gate carabiner with a min. breaking strength of 25kN

HARNES RANGE - SPECIALISED

SPARK - HARN60000

WELDING HARNES



SPECIFIC FEATURES:

- SIZING:** • ONE SIZE FITS ALL
- STANDARDS:** • SANS 50361 | EN 361
- FEATURES:** • 2 Aluminium attachment points: Chest & dorsal D-ring
• Adjustable Aluminium quick-release buckles on the leg & chest straps

MATERIALS:



Harness Webbing: • Flame resistant, 45mm Para-aramid / Meta-aramid blended webbing

Buckles: • Aluminium quick-release buckles

HARNES RANGE - SPECIALISED

KHUMBA - HARN51212

ROPE ACCESS & RESCUE HARNES



SPECIFIC FEATURES:

- SIZING:** • S | M | L | XL
- STANDARDS:** • SANS 50361 | EN 361
SANS 50358 | EN 358
SANS 50813 | EN 813
- FEATURES:** • 5 Aluminium attachment points
• Adjustable Aluminium quick-release buckles on the leg & waist area with adjustable Aluminium buckles on the shoulder and back strap
• Padding in the leg, waist & shoulder areas
• Standing step
• Flame retardant webbing

MATERIALS:



Harness Webbing: • 45mm UV-Resistant & Flame retardant webbing with a minimum breaking load of 3,2 tonnes

Padding: • 5mm laminated foam encased in a Cordura flame retardant nylon/cotton blend fabric

Buckles: • Corrosion-resistant Aluminium buckles

Carabiner: • Corrosion-resistant, Aluminium carabiner with a breaking strength of 22kN

HARNES RANGE - SPECIALISED

ARC - HARN70000

MULTI PURPOSE HARNES



SPECIFIC FEATURES:

- SIZING:** • S | M | L | XL
- STANDARDS:** • SANS 50358 | EN 358
SANS 50361 | EN 361
ASDM F887-13 | ATPV 40Cal/cm²

- FEATURES:** • 4 Aluminium attachment points: Chest & dorsal D-ring with work positioning D-rings
• Adjustable Aluminium quick-release buckles on the leg, waist and abdominal area with adjustable Aluminium buckles on the shoulder and back straps
• Padding in the leg, waist, & shoulder areas
• All attachment points, adjustments & padding are covered in full grain leather

MATERIALS:



Webbing: • Fire retardant & ARC flash rated, 45 mm Para-aramid / Meta-aramid blending webbing

Padding: • 5mm laminated foam encased in full grain leather

Buckles: • Corrosion-resistant Aluminium quick-release buckles with a min. breaking strength of 18kN

D-Ring: • Corrosion-resistant Aluminium D-rings with a min. breaking strength of 22kN

BELTRANGE - PADDED

MINING - CLB01010

MINERS BELT



SPECIFIC FEATURES:

- SIZING:** • ONE SIZE FITS ALL
- FEATURES:** • Rescue Pack and battery strap
• Padded waist area
• Adjustable strap

MATERIALS:



Padding: • 5mm laminated foam to spread pressure over a larger area

Buckles: • Interlocking, corrosion-resistant steel buckles

D-Ring: • Corrosion-resistant Aluminium D-rings with a min breaking strength of 22kN

LANYARD RANGE -EXTENSIO RANGE

CODE: LANY01220

DOUBLE LEG LANYARD



SPECIFIC FEATURES:

SIZING: • 1750MM

STANDARDS: • SANS 50354 | EN 354
SANS 50355 | EN 355
EN 362

FEATURES: • Double leg with scaffold hooks
• Single leg with snap hook
• Shock absorber

MATERIALS:



- Webbing:** • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes
- Lanyard Length:** • 1750mm when shock absorber is intact
- 3450mm when shock absorber is fully deployed
- Hooks:** • Corrosion-resistant steel hooks:
- Scaffolding hooks: 50mm gate opening that can withstand a force of 23kN
- Snap hook: 20mm gate opening that can withstand a force of 22kN

LANYARD RANGE -EXTENSIO RANGE

CODE: LANY01620

ELASTICATED DOUBLE LEG LANYARD



SPECIFIC FEATURES:

SIZING: • 1750MM

STANDARDS: • SANS 50354 | EN 354
SANS 50355 | EN 355
EN 362

FEATURES: • Elasticated double leg with scaffold hooks
• Single leg with snap hook
• Shock absorber

MATERIALS:



- Webbing:** • 25mm UV-resistant polyester webbing with a minimum breaking load of 2,6tonnes
- Lanyard Length:** • 1750mm when shock absorber is intact
- 3450mm when shock absorber is fully deployed
- Hooks:** • Corrosion-resistant steel hooks:
- Scaffolding hooks: 50mm gate opening that can withstand a force of 23kN
- Snap hook: 20mm gate opening that can withstand a force of 22kN

LANYARD RANGE -EXTENSIO RANGE

CODE: LANY01420

ADJUSTABLE DOUBLE LEG LANYARD



SPECIFIC FEATURES:

SIZING: • 1750MM

STANDARDS: • SANS 50354 | EN 354
SANS 50355 | EN 355
EN 362

FEATURES: • Adjustable with double leg scaffold hooks
• Single leg with screw gate carabiner
• Shock absorber

MATERIALS:



- Webbing:** • 25mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes
- Lanyard Length:** • 1400mm – 1750mm (when shock absorber is intact)
- 3450mm when shock absorber is fully deployed
- Hooks:** • Corrosion-resistant steel hooks:
- Scaffolding hooks: 50mm gate opening that can withstand a force of 23kN
- Carabiner:** • Auto-Lock Carabiner: 20mm gate opening that can withstand a force of 22kN

LANYARD RANGE -EXTENSIO RANGE

CODE: LANY01610

ELASTICATED SINGLE LEG LANYARD



SPECIFIC FEATURES:

SIZING: • 1750MM

STANDARDS: • SANS 50354 | EN 354
SANS 50355 | EN 355
EN 362

FEATURES: • Elasticated single leg with scaffold hook
• Single leg with snap hook
• Shock absorber

MATERIALS:



- Webbing:** • 25mm UV-resistant polyester webbing with a minimum breaking load of 2,6tonnes
- Lanyard Length:** • 1750mm when shock absorber is intact
- 3450mm when shock absorber is fully deployed
- Hooks:** • Corrosion-resistant steel hooks:
- Scaffolding hook: 50mm gate opening that can withstand a force of 23kN
- Snap hook: 20mm gate opening that can withstand a force of 22kN

LANYARD RANGE - EXTENSIO RANGE

CODE: ERCS01000

ENDLESS ROUND SLING



SPECIFIC FEATURES:

SIZING: • 1500MM

STANDARDS: • SANS 50795 | EN 795

FEATURES: • 38mm seatbelt webbing encased into 50mm tubular webbing
• Supplied as a set of two

MATERIALS:



- Webbing:** • 45mm UV-resistant polyester webbing with a minimum breaking strength of:
- Straight – 25kN
 - Basket – 50kN
 - Backlash – 20kN
- Length:** • 1500mm per sling

LANYARD RANGE - SPECIALISED

SPARK - LANY05220

ARC / WELDING LANYARD



SPECIFIC FEATURES:

SIZING: • 1750MM

STANDARDS: • SANS 50354 | EN 354
SANS 50355 | EN 355
EN 362
ASDM F887-13 | ATPV
40Cal/cm²

FEATURES: • Double leg with Aluminium pylon hooks
• Single leg with Aluminium auto-lock carabiner
• Shock absorber
• Fire retardant & ARC flash rated webbing

MATERIALS:



- Webbing:** • Fire retardant & ARC flash rated webbing, 25mm Para-aramid/Meta-aramid blended webbing with a minimum breaking load of 2,6 tonnes
- Shock cover:** • Full grain leather sock to protect shock absorber from burns created by an ARC flash or sparks
- Lanyard Length:** • 1750mm (when shock absorber is intact)
- 3450mm when shock absorber is fully deployed
- Hooks:** • Aluminum pylon hooks: 60mm gate opening that can withstand a force of 23kN
- Carabiner:** • Auto-Lock Carabiner: 20mm gate opening that can withstand a force of 22kN

LANYARD RANGE -EXTENSIO RANGE

CODE: WPSR01010

WORK POSITIONING LANYARD



SPECIFIC FEATURES:

SIZING: • MAX 2000MM

STANDARDS: • SANS 50354 | EN 354
EN 362

FEATURES: • Two snap hooks
• Adjustable webbing with pvc protector

MATERIALS:



- Webbing:** • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes
- Lanyard Adjustment:** • 800mm - 2000mm utilising a floating buckle
- Buckle:** • Corrosion-resistant steel buckle
- Protective Sleeve:** • PVC material for enhanced durability
- Hooks:** • Corrosion-resistant steel Snap hooks with 20mm gate opening that can withstand a force of 22kN

LANYARD RANGE -SPECIALISED

KHUMBA LANYARD - LANY05420

FIRE RETARDANT LANYARD



SPECIFIC FEATURES:

SIZING: • 1750MM

STANDARDS: • SANS 50354 | EN354
SANS 50355 | EN355
EN362

FEATURES: • Double leg with Aluminium pylon hooks
• Single connector with auto-lock carabiner hook connector
• Shock absorber
• Fire retardant webbing

MATERIALS:



- Webbing:** • Fire retardant, 25mm Para-aramid/Meta-aramid blended webbing with a minimum breaking load of 2,6 tonnes
- Lanyard Length:** • 1400mm – 1750mm (when shock absorber is intact)
- 3450mm when shock absorber is fully deployed
- Hooks:** • Aluminum pylon hooks: 60mm gate opening that can withstand a force of 23kN
- Carabiner:** • Auto-Lock Carabiner: 20mm gate opening that can withstand a force of 22kN



QUALITY ENGINEERING THAT FITS



ENGINEERED WITH PURPOSE

CONTISUITRANGE - 65/35 POLYCOTTON

CODE: OJ12927



SPECIFIC FEATURES:

FABRIC: • 65/35 POLY COTTON

COLOURS: • Black | Emerald Green | Grey | Khaki | Navy | Orange | Red
Royal Blue

SIZES: • 32 - 60

CONTISUITRANGE - 65/35 POLYCOTTON

TRI-REFLECT WORK JACKET CODE: OJ12928

CODE: OJ12928



IN STOCK

MADE TO ORDER

SPECIFIC FEATURES:

FABRIC: • 65/35 POLY COTTON

REFLECTIVE: 19mm VizLite™ reflective tape – Lime/Silver/Lime

COLOURS: • Emerald Green | Grey | Khaki | Navy | Orange | Red
Royal Blue | Black

CLOSURES: • Concealed YKK aluminium zip – Type 5

POCKETS: • Press stud front pockets
• Extended large front pockets

SIZES: • 32 - 60

COMFORT: • Triple stitched elbows for enhanced durability
• Bar tacked at stress points for extra strength

CONTISUITRANGE - 65/35 POLYCOTTON

CODE: OJ13070



SPECIFIC FEATURES:

FABRIC: • 65/35 POLY COTTON

COLOUR: • Bottle Green & Khaki | Navy & Khaki | Stone & Khaki

SIZES: • 32- 60

CONTISUITRANGE - 65/35 POLYCOTTON

CODE: OT12935



SPECIFIC FEATURES:

FABRIC: • 65/35 POLY COTTON

COLOURS: • Black | Emerald Green | Grey | Khaki | Navy | Orange | Red
Royal Blue

SIZES: • 28 - 56

CONTISUITRANGE - 65/35 POLYCOTTON

CODE: OT12936



SPECIFIC FEATURES:

FABRIC: • 65/35 POLY COTTON

REFLECTIVE: 19mm VizLite™ reflective tape – Lime/Silver/Lime

COLOURS: • Emerald Green | Grey | Khaki | Navy | Orange | Red
Royal Blue | Black

SIZES: • 28 - 56

CONTISUITRANGE - 65/35 POLYCOTTON

CODE: OT13071



SPECIFIC FEATURES:

FABRIC: • 65/35 POLY COTTON

COLOUR: • Bottle Green & Khaki | Navy & Khaki | Stone & Khaki

SIZES: • 28 - 56

CONTISUITRANGE - POLYVISCOSE

CODE: OJ12926



SPECIFIC FEATURES:

- FABRIC:** • POLY VISCOSE ACID RESISTANT
COLOUR: • Bottle Green
SIZES: • 32 - 60

CONTISUITRANGE - POLYVISCOSE

CODE: OT12934



SPECIFIC FEATURES:

- FABRIC:** • POLY VISCOSE ACID RESISTANT
COLOUR: • Bottle Green
SIZES: • 28 - 56

CONTISUITRANGE - DENIM 100% COTTON

CODE: OJ12925



SPECIFIC FEATURES:

- FABRIC:** • 100% COTTON
REFLECTIVE: 19mm VizLite™ reflective tape – Lime/Silver/Lime
COLOUR: • Denim
SIZES: • 32 - 60

CONTISUITRANGE - DENIM 100% COTTON

CODE: OT12933




SPECIFIC FEATURES:

- FABRIC:** • 100% COTTON
REFLECTIVE: 19mm VizLite™ reflective tape – Lime/Silver/Lime
COLOUR: • Denim
SIZES: • 28 - 56

CONTISUITRANGE - J54 100% COTTON

CODE: OJ12931



SPECIFIC FEATURES:

- FABRIC:** • J54 100% COTTON
COLOUR: • Navy | Royal Blue
SIZES: • 32 - 60

CONTISUITRANGE - J54 100% COTTON

CODE: OT12940



SPECIFIC FEATURES:

- FABRIC:** • J54 100% COTTON
COLOUR: • Navy | Royal Blue
SIZES: • 28 - 56

CONTISUITRANGE - D59 100% COTTON

CODE: OJ12930



SPECIFIC FEATURES:

- FABRIC:** • D59 100% COTTON FLAME RETARDANT & ACID RESISTANT
REFLECTIVE: 48mm VizLite™ reflective tape
COLOURS: • Navy
SIZES: • 32 - 60

CONTISUITRANGE - D59 100% COTTON

CODE: OT12938



SPECIFIC FEATURES:

- FABRIC:** • D59 100% COTTON FLAME RETARDANT & ACID RESISTANT
REFLECTIVE: 48mm VizLite™ reflective tape
COLOURS: • Navy
SIZES: • 28 - 56

CONTISUITRANGE - J54 100% COTTON

CODE: OJ12932



SPECIFIC FEATURES:

- FABRIC:** • J54 100% COTTON
REFLECTIVE: 19mm VizLite™ reflective tape – Lime/Silver/Lime
COLOUR: • Navy | Royal Blue
SIZES: • 32 - 60

CONTISUITRANGE - J54 100% COTTON

CODE: OT12939



SPECIFIC FEATURES:

- FABRIC:** • J54 100% COTTON
REFLECTIVE: 19mm VizLite™ reflective tape – Lime/Silver/Lime
COLOUR: • Navy | Royal Blue
SIZES: • 28 - 56

CONTISUITRANGE - HIGH VIZ

CODE: OJ13072



SPECIFIC FEATURES:

- FABRIC:** • LUMINOUS FABRIC – 50/50 POLY COTTON
 • BASE FABRIC – 65/35 POLY COTTON
REFLECTIVE: 50mm VizLite™ reflective tape
COLOURS: • Navy & Lime | Navy & Orange
SIZES: • 32 - 60

CONTISUITRANGE - HIGH VIZ

CODE: OT13073



SPECIFIC FEATURES:

- FABRIC:** • LUMINOUS FABRIC – 50/50 POLY COTTON
 • BASE FABRIC – 65/35 POLY COTTON
REFLECTIVE: 50mm VizLite™ reflective tape
COLOURS: • Navy & Lime | Navy & Orange
SIZES: • 28 - 56

BOILERSUITRANGE - J54 100% COTTON

CODE: OB12922



SPECIFIC FEATURES:

- FABRIC:** • J54 100% COTTON
REFLECTIVE: 19mm VizLite™ reflective tape
COLOUR: • Navy
SIZES: • 32 - 60

BOILERSUITRANGE - D59 100% COTTON

CODE: OB12921



SPECIFIC FEATURES:

- FABRIC:** • D59 100% COTTON FLAME RETARDANT & ACID RESISTANT
REFLECTIVE: 48mm VizLite™ reflective tape
COLOUR: • Navy
SIZES: • 32 - 60

DUSTCOATRANGE - 65/35 POLY COTTON

CODE: OD13069



SPECIFIC FEATURES:

- FABRIC:** • 65/35 POLY COTTON
COLOUR: • Grey | Navy | Royal Blue | White
SIZES: • 32 - 60

DUSTCOATRANGE - 65/35 POLY COTTON

CODE: OD13068



SPECIFIC FEATURES:

- FABRIC:** • 65/35 POLY COTTON ACID RESISTANT
COLOUR: • White
SIZES: • 32 - 60

HIGH VISIBILITY SHIRTS RANGE

CODE: OS13077



SPECIFIC FEATURES:

- FABRIC:** • LUMINOUS FABRIC – 50/50 POLY COTTON
 • BASE FABRIC – 100% COTTON
REFLECTIVE: 48mm VizLite™ reflective tape
COLOURS: • Navy & High VIZ Yellow | Navy & High VIZ Orange
SIZES: • 32 - 60

65/35 POLY COTTON:
 This fabric comprises 35% cotton and 65% polyester. Cotton is a natural fibre that is known for its breathability, while polyester is a man-made fibre that is known for its resilience and washability. When polyester is blended with cotton, the resultant fabric offers better crease resistance.

J54:
 This fabric is made from 100% cotton and is SABS approved. As a natural fibre cotton is soft, highly breathable and acts as an insulator. The benefit of this fabric is that the wearer will remain cool in the summer months and warm in winter.

D59:
 This fabric is made from 100% cotton and is SABS approved. The fabric is treated with either an acid resistant or flame retardant or both acid resistant and flame retardant finish, depending on the wearer's requirements.

POLY VISCOSE:
 This fabric is made from a combination of polyester and viscose. Similar to cotton in its feel, the material is man-made and absorbs perspiration quickly, making it skin-friendly, but with little thermal properties.

HIGH VIZ:
 The luminous fabric used in our HighVIZ range comprises 50% polyester and 50% cotton. This is a highly visible fabric that offers extreme visibility in low to no light conditions. This fabric is applied to one or two types of base fabrics; either 65/35 poly cotton or 100% cotton.

SIZE CHART

JACKETS

CHEST MEASUREMENTS

INCHES	32	34	36	38	40	42	44
CM	82	87	92	97	102	107	112
SIZE	XS	S	M	L			

INCHES	46	48	50	52	54	56	58	60
CM	117	122	127	132	137	142	147	152
SIZE	XL	XXL	XXXL	XXXXL				

NOTE: Jackets are to be ordered by chest size and trousers to be ordered by waist size. Use trouser's waist measurement and increase by two sizes to determine corresponding jacket chest size.

TROUSERS

WAIST MEASUREMENTS

INCHES	28	30	32	34	36	38	40
CM	72	77	82	87	92	97	102

INCHES	42	44	46	48	50	52	54	56
CM	107	112	117	122	127	132	137	142

NOTE: Trousers to be ordered by waist size and jackets to be ordered by chest size. Use trouser's waist measurement and increase by two sizes to determine corresponding jacket chest size.

BOILER SUITS

CHEST MEASUREMENTS

INCHES	30	32	34	36	38	40	42
CM	77	82	87	92	97	102	107
SIZE	XS	S	M	L			

INCHES	44	46	48	50	52	54	56	58	60	62
CM	112	117	122	127	132	137	142	147	152	157
SIZE	XL	XXL	XXXL	XXXXL	XXXXXL					

CORRELATING WAIST MEASUREMENT:

INCHES	28	30	32	34	36	38	40
CM	72	77	82	87	92	97	102


INCHES	42	44	46	48	50	52	54	56	58
CM	107	112	117	122	127	132	137	142	147

NOTE: Boiler suits to be ordered by chest measurement. Check chest measurement table for corresponding waist size. Use trouser's waist measurement and increase by two sizes to determine corresponding jacket chest size.



CHEMICAL RESISTANCE TABLE

THIS TABLE IS ONLY RELEVANT TO POLYURETHANE (PU) SOLES



Acetic Acid 3 n	3	Diesel Oil	5	Methyl Glycol	2
Acetone	2	Dimethyl Acetamide	1	Methyl Glycol Acetate	2
Aluminium Chloride 10% Sol.	4	Dimethyl Formamide	1	Methylene Chloride	2
Ammonia 3 n	5	Distilled Water	5	Mineral Oil	5
Ammonium Chloride 10% Sol.	5	Ethanol	3	Nitric Acid 3 n	1
Aniline	2	Ether	3	N-Methyl Pyrrolidone	1
ASTM-Fuel A	5	Ethyl Acetate	2	Ozone	5
ASTM-Fuel B	4	Ethylene Chloride	3	Paraffin Oil	5
ASTM-Fuel C	3	Ferric Chloride 10% Sol.	4	Perchloroethylene	2
ASTM-Oil 1	5	Formic Acid 3 n	2	Petroleum	5
ASTM-Oil 2	5	Freon 12	3	Petroleum Ether	5
ASTM-Oil 3	5	Freon 22	3	Phosphoric Acid 3 n	3
Benzene	2	Gear Box Oil SAE 90	5	Potassium Chloride 10% & 40% Sol.	5
Benzyl Alcohol	1	Glycerine	5	Potassium Dichromate 10% Sol.	5
Bleach	5	Glycol	5	Potassium Hydroxide 3 n	5
Brake Fluid ATE	5	Hydrochloric Acid 3 n	5	Potassium Nitrate	4
Brake Fluid ATS	5	Hydrogen Peroxide 3%	5	Potassium Permanganate 5% Sol.	2
Butane	4	Iso-Octane Fuel 1	5	Propane	4
Butyl Acetate	2	Iso-Octane 70% : 30% Toluene = Fuel 2	4	Pyridine	1
Butyl Alcohol	3	Iso-Octane 50% : 50% Toluene = Fuel 3	3	Sea Water (Technical)	5
Calcium Chloride 10% & 40% Sol.	5	Iso-Propanol	4	Sodium Bisulphate 10% Sol.	4
Carbon Disulphide	3	Kerosine	5	Sodium Chloride 10% Sol.	5
Carbon Tetrachloride	2	Lactic Acid 3 n	1	Sodium Hypochlorite Sol. PH 13	3
Caustic Soda Sol. 10%	5	Lubricating Grease: Calcium based	5	Sodium Sulphite	4
Chlorobenzene	2	: Lithium based	5	Sulphuric Acid 3 n	1
Chloroform	2	: Sodium based	5	Terpentine (Pine Oil)	4
Chromic Acid 3 n	2	Magnesium Chloride 10% & 30% Sol.	5	Tetrachlorethylene	2
Citronic Acid 3 n	4	Methane	4	Tetrahydrofuran	2
Cyclohexane	4	Methanol	4	Toluene	2
Cyclohexanon	2	Methyl Acetate	2	Trichloroethylene	2
Decalin	3	Methyl Ethyl Ketone	2	Xylene	2

If you are exposed to any of the acids, oils or chemicals that rate 1, 2 or 3 on the table we recommend a rubber sole shoe/boot. Please consult the Extremewear section.

The above table should be used as a general guide only. Performance in the actual working environment will depend upon the following: temperature of chemicals, concentrations of chemicals and duration of exposure.



SAFETYWEAR

